

according to the Global Harmonized System (and with all of the information required by the HPR)

Revision Date 06/17/2018

Version 1.5

SECTION 1.Identification

Product identifier

Product number BX1805

Product name tert-Butyl Alcohol GR ACS

CAS-No. 75-65-0

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

Details of the supplier of the safety data sheet

Company Millipore (Canada) Ltd | 109 Woodbine Downs Blvd. Unit 5 | Etobicoke

| Ontario M9W 6Y1 | Canada | General Inquiries: +1 800-645-5476 | Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.

Emergency telephone 800-424-9300 CHEMTREC (USA)

+1-703-527-3887 CHEMTREC (International)

24 Hours/day; 7 Days/week

SECTION 2. Hazards identification

GHS Classification

Flammable liquid, Category 2, H225

Acute toxicity, Category 4, Inhalation, H332

Eye irritation, Category 2A, H319

Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system, Central nervous

system, H335 H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms





Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula (CH₃)₃COH C₄H₁₀O (Hill)

Molar mass 74.12 g/mol

Hazardous ingredients

Chemical name (Concentration)

CAS-No.

tert-Butanol (>= 90 % - <= 100 %)

75-65-0

SECTION 4. First aid measures

Description of first-aid measures

Inhalation

After inhalation: fresh air. Call in physician.

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name *tert*-Butyl Alcohol GR ACS

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Ingestion

After swallowing: immediately make victim drink water (two glasses at most). Subsequently administer: activated charcoal (20 - 40 g in 10% slurry). Consult a physician.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

irritant effects, Cough, respiratory paralysis, Shortness of breath, Drowsiness, Dizziness, narcosis, inebriation, Nausea, Vomiting, cardiovascular disorders, CNS disorders

Indication of any immediate medical attention and special treatment needed

Laxative: Sodium sulfate (1 tablespoon/1/4 I water).

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at ambient temperatures.

Development of hazardous combustion gases or vapors possible in the event of fire.

Advice for firefighters

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Environmental precautions

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Store at room temperature.

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

| Ingredients | | | |
|----------------------|--------------------------------------|----------------------|---------|
| Basis | Value | Threshold limits | Remarks |
| tert-Butanol 75-65-0 | | | |
| CAD AB OEL | Time Weighted Average (TWA): | 100 ppm 303 mg/m³ | |
| CAD BC OEL | Time Weighted Average (TWA): | 100 ppm | |
| CAD MB OEL | Time Weighted Average (TWA): | 100 ppm | |
| CAD ON OEL | Time Weighted Average (TWAEV): | 100 ppm | |
| | Short Term Exposure Limit (STEV): | 150 ppm | |
| OEL (QUE) | Time Weighted Average (TWA): | 100 ppm 303 mg/m³ | |
| | | | |

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name *tert*-Butyl Alcohol GR ACS

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Eye/face protection
Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber Glove thickness: 0.40 mm Break through time: 480 min

splash contact:

Glove material: polychloroprene

Glove thickness: 0.65 mm Break through time: 240 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 730 Camatril® -Velours (full contact), KCL 720 Camapren® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:

Flame retardant antistatic protective clothing.

SECTION 9. Physical and chemical properties

Physical state solid

Color colorless

Odor camphor-like

Odor Threshold 71 ppm

pH at 68 °F (20 °C)

neutral

Melting point/range 75 - 77 °F (24 - 25 °C)

Boiling point/boiling range 178 - 181 °F (81 - 83 °C)

at 1,013 hPa

Flash point 57 °F (14 °C)

Method: c.c.

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name *tert*-Butyl Alcohol GR ACS

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit 2.3 %(V)

Upper explosion limit 8.0 %(V)

Vapor pressure 40.7 hPa

at 68 °F (20 °C)

Relative vapor density 2.56

Density 0.78 g/cm3

at 68 °F (20 °C)

Relative density No information available.

Water solubility at 68 °F (20 °C)

soluble

Partition coefficient: n-

octanol/water

log Pow: 0.30

OECD Test Guideline 107

Bioaccumulation is not expected.

Autoignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic 3.3 mPa.s

at 86 °F (30 °C)

Explosive properties Not classified as explosive.

Oxidizing properties none

Ignition temperature 914 °F (490 °C)

Method: DIN 51794

SECTION 10. Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

Possibility of hazardous reactions

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

Violent reactions possible with:

Alkali metals, Alkaline earth metals, Strong acids, Aluminum, Strong oxidizing agents

Conditions to avoid

Warming.

Incompatible materials

rubber, various plastics

Hazardous decomposition products

Peroxides

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Acute oral toxicity

LD50 Rat: 2,733 mg/kg

US-EPAacute oral toxicity cat. 5 (Regulation (EC) No 1272/2008, Annex VI)

Symptoms: Nausea, Vomiting

Acute inhalation toxicity

LC50 Rat: 36 mg/l10000 ppm; 4 h; vapor

OPPTS 870.1300

(Regulation (EC) No 1272/2008, Annex VI)

Irritating to respiratory system.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Skin irritation

Rabbit

Result: No irritation

Draize Test

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eve irritation

Rabbit

US-EPA

Causes serious eye irritation.

Sensitization

Sensitization test (Magnusson and Kligman): Guinea pig

Result: negative

Method: OECD Test Guideline 406

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

Genotoxicity in vivo Micronucleus test

Mouse

Result: negative

Genotoxicity in vitro

In vitro mammalian cell gene mutation test

MOUSE LYMPHOMA TEST

Result: negative

Method: OECD Test Guideline 476

Specific target organ systemic toxicity - single exposure

May cause respiratory irritation.

Target Organs: Respiratory system

May cause drowsiness or dizziness.

Target Organs: Central nervous system

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

egual to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

Further information

After absorption:

CNS disorders, drop in blood pressure, Drowsiness, Dizziness, inebriation, respiratory paralysis, cardiovascular disorders, narcosis

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

Toxicity to fish

flow-through test LC50 Pimephales promelas (fathead minnow): > 961 mg/l; 96 h

Analytical monitoring: yes OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

static test EC50 Daphnia magna (Water flea): 933 mg/l; 48 h

Analytical monitoring: yes

Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae

IC50 Desmodesmus subspicatus (green algae): > 1,000 mg/l; 72 h (IUCLID)

Toxicity to bacteria

EC10 Pseudomonas putida: 6,900 mg/l; 16 h (External MSDS)

Persistence and degradability

Biodegradability > 99.9 %; 19 d

OECD Test Guideline 302B Readily eliminated from water

Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: 0.30

OECD Test Guideline 107

Bioaccumulation is not expected.

Mobility in soil

No information available.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)

UN 1120
Proper shipping name BUTANOLS

Class 3
Packing group II
Environmentally hazardous ---

Air transport (IATA)

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

UN 1120
Proper shipping name BUTANOLS

Class 3
Packing group II
Environmentally hazardous -Special precautions for user no

Sea transport (IMDG)

UN 1120
Proper shipping name BUTANOLS

Class 3
Packing group II
Environmentally hazardous -Special precautions for user yes
EmS F-E S-D

SECTION 15. Regulatory information

United States of America

Canada

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Labeling

Hazard pictograms





Signal Word
Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number BX1805 Version 1.5

Product name tert-Butyl Alcohol GR ACS

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date06/17/2018

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.